

A close-up photograph of a heavy-duty metal chain, likely made of steel, with large, interlocking links. The chain is set against a dark blue background with a subtle geometric pattern. The lighting highlights the metallic texture and the circular ends of the links.

**American
Chains**

www.americanchains.com

FORESTRY AND INDUSTRIAL



Super Stud™

The American Chains™ 5/8" (16mm) Super Stud™ model features 3/4" (19mm) oversized studs. Super Stud™ chain is recommended for harvester/forwarder applications in addition to skidders and loaders, where an open pattern for ease of cleaning is needed. Excellent traction on ice and rock.

Standard

5/8" (16mm) Tag Chain with 3/4" (19mm) Studs



Single Net™

Double Net™

Triple Net™

American Chains™ Net™ chains are now available in single, double, or triple Net™ patterns, in 9/16" (14mm), 5/8" (16mm), or 3/4" (19mm) tag options. All feature six aggressive studs per section for maximum traction. Excellent tire protection with superior traction.

Single Net

Available in 9/16" (14mm), 5/8" (16mm), or 3/4" (19mm) tag chain. Six stud pattern provides superior traction.

Double Net

Available in 9/16" (14mm), 5/8" (16mm), or 3/4" (19mm) tag chain. Six stud pattern provides superior traction.

Triple Net

Available in 9/16" (14mm), 5/8" (16mm), or 3/4" (19mm) tag chain. Six stud pattern provides superior traction.



Combo™ Chain

An industry first of combination ring and stud chain allowing for traction in all types of terrain and conditions. With the aggressive ring design, coupled with studded tag chain, Combo™ Chain performs in mud or snow, and rock or ice, and is suitable for all heavy duty applications. Large heavy duty rings and lugs with 3/4" (19mm) studs on both the 5/8" (16mm) and 3/4" (19mm) tag models. Also available in dual side by side rings in wider flotation tire sizes.

7 links of 5/8" (16mm) tag chain

1 1/8" x 10" (28.5 x 254mm) rings, 4 - 3/4" (19mm) studs between rings, Lugs are 5/8" (16mm) thick x 1 3/4" (44.5 mm) h x 2 1/2" (63.5mm)w

7 links of 3/4" (19mm) tag chain

1 1/4" x 10" (32 x 254mm) rings, 4 - 3/4" (19mm) Studs between rings, Lugs that are 5/8" (16mm) thick x 2" (51mm)h x 3" (76mm)w



Tight Ring Bear Paw™

Standard Ring Bear Paw™

Economy Ring Bear Paw™

Bear Paw™ Ring chains are available in three different models, all with 5/8" (16mm) tag chain, for medium duty applications in mud or snow. Bear Paw™ Tight-Ring offers smooth operator ride with its three links 5/8" (16mm) tag configuration due to minimal distance between rings. Bear Paw™ Standard Ring, with industry standard five links of 5/8" (16mm) tag chain, delivers traction and performance with value. Bear Paw™ Economy Ring, with seven links of 5/8" (16mm) tag, provides the traction required while also offering greater savings.

Tight Ring

3 links of 5/8" (16mm) tag chain, 1" x 10" (25.4 x 254mm) rings with Lugs 5/8" (16mm) thick x 1 1/2" (38mm)h x 2 1/2" (63.5mm)w

Standard Ring

5 links of 5/8" (16mm) tag chain, 1" x 10" (25.4 x 254mm) rings with Lugs 5/8" (16mm) thick x 1 1/2" (38mm)h x 2 1/2" (63.5mm)w

Economy Ring

7 links of 5/8" (16mm) tag chain, 1" x 10" (25.4 x 254mm) rings with Lugs 5/8" (16mm) thick x 1 1/2" (38mm)h x 2 1/2" (63.5mm)w

AGRICULTURAL



ForesTrac® Studded

American Chains™ ForesTrac® studded tractor tire chains are available with 1/2" tag chain to meet any traction requirements, especially rock or ice. American Chains recommends customer checks for adequate clearance before purchasing these aggressive off road tractor chains.

Standard Pattern

1/2" (12mm) Tag Chain with Four 9/16" (14mm) studs



American Chains is TCR's newest line of tire chains for forestry, industrial, and agricultural equipment. American Chains™ feature hardened Boron Alloy steel for maximum durability.



ForesTrac® Ring

American Chains™ ForesTrac® ring tire chains are available with 1/2" tag chain with 1" by 10" ring or 7/8" by 8" ring to meet any traction requirements, especially mud or snow. American Chains recommends customer checks for adequate clearance before purchasing these aggressive off road tractor chains.

1/2" (12mm) Tag chain and a 1" x 10" (25.4 x 254mm) Ring

Lugs are 1/2" (12mm) thick x 2 1/2" (63.5mm) w x 1 1/4" (31.75mm) h

1/2" (12mm) Tag chain and a 7/8" x 8" (16 x 203mm) Ring

Lugs are 1/2" (12mm) thick x 2 1/2" (63.5mm) w x 1 1/4" (31.75mm) h



www.americanchains.com

American
 **Chains**

Offered Exclusively by:



207 465 7276

www.tirechainsrequired.com